

## Energy Independence and Security Act of 2007

October 12, 2009

On December 19, 2007, the Energy Independence and Security Act of 2007 (EISA) was signed into law. EISA applies to motors manufactured after December 19, 2010.

### A summary of new EISA standards for motors used today:

- General purpose motors (subtype I) with a power rating of 1-200 horsepower must have a nominal full-load efficiency that meets or exceeds NEMA Premium efficiency levels. See NEMA MG1 (2006) Table 12-12.
- General purpose motors (subtype II), with a power rating of 1-200 horsepower shall have a nominal full-load efficiency that meets or exceeds efficiencies defined in NEMA MG1 (2006) Table 12-11. Subtype II motors now include:
  - U-Frame motor
  - Design C motor
  - Close-Coupled pump motor
  - Footless motor
  - Vertical solid-shaft normal thrust motor (tested in a horizontal configuration)
  - 8-pole motor (900 RPM)
  - Poly-phase motor with voltage of no more than 600 volts (other than 230 or 460 volts)
- Fire pump motors shall have nominal full-load efficiency no less than as defined in NEMA MG1 (2006) Table 12-11.
- NEMA Design B, general purpose electric motors, with a power rating of 200-500 horsepower shall have a nominal full-load efficiency that is not less than as defined in NEMA MG1 (2006) Table 12-11.

**ESR Motor Systems, LLC**

648 E. White St. • Rock Hill, SC 29730  
(803) 324-7676 • FAX: (803) 324-3259

**NEMA MG-1 Table 12-12 Full-Load Efficiencies for 60Hz NEMA Premium Efficient Electric Motors Rated 600 Volts or less (Random Wound)**

Motor Horsepower	Nominal Full-Load Efficiency					
	Open Motors			Enclosed Motors		
	2 Pole	4 Pole	6 Pole	2 Pole	4 Pole	6 Pole
1	77.0	85.5	82.5	77.0	85.5	82.5
1.5	84.0	86.5	86.5	84.0	86.5	87.5
2	85.5	86.5	87.5	85.5	86.5	88.5
3	85.5	89.5	88.5	86.5	89.5	89.5
5	86.5	89.5	89.5	88.5	89.5	89.5
7.5	88.5	91.0	90.2	89.5	91.7	91.0
10	89.5	91.7	91.7	90.2	91.7	91.0
15	90.2	93.0	91.7	91.0	92.4	91.7
20	91.0	93.0	92.4	91.0	93.0	91.7
25	91.7	93.6	93.0	91.7	93.6	93.0
30	91.7	94.1	93.6	91.7	93.6	93.0
40	92.4	94.1	94.1	92.4	94.1	94.1
50	93.0	94.5	94.1	93.0	94.5	94.1
60	93.6	95.0	94.5	93.6	95.0	94.5
75	93.6	95.0	94.5	93.6	95.4	94.5
100	93.6	95.4	95.0	94.1	95.4	95.0
125	94.1	95.4	95.0	95.0	95.4	95.0
150	94.1	95.8	95.4	95.0	95.8	95.8
200	95.0	95.8	95.4	95.4	96.2	95.8
250	95.0	95.8	95.4	95.8	96.2	95.8
300	95.4	95.8	95.4	95.8	96.2	95.8
350	95.4	95.8	95.4	95.8	96.2	95.8
400	95.8	95.8	95.8	95.8	96.2	95.8
450	95.8	96.2	96.2	95.8	96.2	95.8
500	95.8	96.2	96.2	95.8	96.2	95.8

**NEMA MG-1 Table 12-11 Full-Load Efficiencies of Energy Efficient Motors**

Motor Horsepower	Nominal Full-Load Efficiency							
	Open Motors				Enclosed Motors			
	2 Pole	4 Pole	6 Pole	8 Pole	2 Pole	4 Pole	6 Pole	8 Pole
1	-	82.5	80.0	74.0	75.5	82.5	80.0	74.0
1.5	82.5	84.0	84.0	75.5	82.5	84.0	85.5	77.0
2	84.0	84.0	85.5	85.5	84.0	84.0	86.5	82.5
3	84.0	86.5	86.5	86.5	85.5	87.5	87.5	84.0
5	85.5	87.5	87.5	87.5	87.5	87.5	87.5	85.5
7.5	87.5	88.5	88.5	88.5	88.5	89.5	89.5	85.5
10	88.5	89.5	90.2	89.5	89.5	89.5	89.5	88.5
15	89.5	91.0	90.2	89.5	90.2	91.0	90.2	88.5
20	90.2	91.0	91.0	90.2	90.2	91.0	90.2	89.5
25	91.0	91.7	91.7	90.2	91.0	92.4	91.7	89.5
30	91.0	92.4	92.4	91.0	91.0	92.4	91.7	91.0
40	91.7	93.0	93.0	91.7	91.7	93.0	93.0	91.0
50	92.4	93.0	93.0	91.7	92.4	93.0	93.0	91.7
60	93.0	93.6	93.6	92.4	93.0	93.0	93.6	91.7
75	93.0	94.1	93.6	93.6	93.0	94.1	93.6	93.0
100	93.0	94.1	94.1	93.6	93.6	94.5	94.1	93.0
125	93.6	94.5	94.1	93.6	94.5	94.5	94.1	93.6
150	93.6	95.0	94.5	93.6	94.5	95.0	95.0	93.6
200	94.5	95.0	94.5	93.6	95.0	95.0	95.0	94.1
250	94.5	95.4	95.4	94.5	95.4	95.0	95.0	94.5
300	95.0	95.4	95.4	-	95.4	95.4	95.0	-
350	95.0	95.4	95.4	-	95.4	95.4	95.0	-
400	95.4	95.4	-	-	95.4	95.4	-	-
450	95.8	95.8	-	-	95.4	95.4	-	-
500	95.8	95.8	-	-	95.4	95.8	-	-